



MINI 150 Encoder

User's Manual

<u>Preface</u>

About This Manual

This manual provides introductions to users about how to operate the device correctly. The content includes an introduction to product installation, product characteristics and product settings, etc.

Intended Readers

This manual is suggested to be studied by the following readers:

- Technical Service Engineer
- Maintenance Engineer
- Test Engineer
- Sales Engineer

Important

• Avoid personal injury and product damage! Do not proceed beyond any symbol until

you fully understand the indicated conditions. A You may find this symbol in the document that accompanies this product. This symbol indicates important operating or maintenance instructions.

- Please use good quality cables and make sure the connector is in good condition.
- Please do not use a power supply that doesn't match the input requirement.
- Please do not open the encoder.
- Specifications and functions may be changed for improvement without notice in advance.



Notices

• Trademark Acknowledgments

All trademarks shown in this manual are trademarks of their respective owners.

• Publication Disclaimer

Our company assumes no responsibility for errors or omissions that may appear in this publication. We reserve the right to change this publication at any time without notice. This document is not to be construed as conferring by implication, estoppel, or otherwise any license or right under any copyright or patent, whether or not the use of any information in this document employs an invention claimed in any existing or later issued patent.

• Copyright

Information in this publication is subject to change without notice. No part of this publication may be reproduced or transmitted in any form, by photocopy, microfilm, xerography, or any other means, or incorporated into any information retrieval system, electronic or mechanical, for any purpose, without the express permission of our company.

Safety Instructions

This warning symbol means danger. You are in a situation that could cause bodily injury. Before you work on any equipment, be aware of the hazards involved with electrical circuitry and be familiar with standard practices for preventing accidents.

Electric Shock Hazard

This equipment meets applicable safety standards. Refer to this equipment's Identification label or contact factory for details about regulatory compliance approvals.

MARNING:

To reduce risk of electric shock, perform only the instructions that are included in the operating instructions. Refer all servicing and installation to qualified service personnel only.

Electric shock can cause personal injury or even death. Avoid direct contact with dangerous voltages at all times. The protective ground connection, where provided, is essential to safe operation and must be verified before connecting the power supply.

Know the following safety warnings and guidelines:

- Only trained and qualified personnel should be allowed to install, replace, or service this equipment.

- Only qualified service personnel are allowed to remove encoder covers and access any of the components inside.

- There are no user-serviceable parts inside. Do not open.

Important Safety Instructions

- Read these instructions.
- Keep these instructions.
- Heed all warnings.
- Follow all instructions.
- Do not use this apparatus near water.
- Clean only with dry cloth.
- Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
- Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
- Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
- Only use attachments/accessories specified by the manufacturer.
- Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
- Unplug this apparatus during lightning storms or when unused for long periods of time.
- Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

WARNING:

A

To reduce the risk of fire or electric shock, do not expose this apparatus to rain or moisture. The apparatus shall not be exposed to dripping or splashing and no objects filled with liquids, such as vases, shall be placed on the apparatus.

10	VERVIEV	N	8
	1.1	Introduction	8
	1.2	Architecture	8
	Front F	Panel	8
	Rear Pa	anel	8
2 IN	STALLAT	TION	9
	2.1 Ins	tallation Procedure	9
	2.2 Pre	eparation before Installation	9
	2.3 Che	eck Package and Contents	10
	2.4 Equ	uipment Wiring and Connection	10
	2.4.1 P	Power Connection	10
	2.4.2 D	DC Power Connection	10
	2.4.30	Connection Setup for Web Management	11
	2.4.4 C	Connection Setup for HDMI/CVBS/SDI signal input	11
3 OI	PERATIO	DN GUIDE	11
	3.1 Op	perating the Front Panel Interface	11
	3.	.1.1 Powering Up and Initialization	11
	3.	.1.2Front Panel Menu Structure	12
	3.2 Op	perating the WEB Interface	13
	3.	.2.1 Access Interface	13
	3.	.2.2 Main Interface	14
	3.	.2.3 Live Mode	15
	3.	.2.4 Playback mode	21
	3.	.3.5 Recording Mode	23
	3.	.3.6 System	24

Contents

1 OVERVIEW

1.1 Introduction

The Niagara Mini 150 is a highly effective encoder for video and audio processing which supports HDMI/SDI/CVBS standard input sources and outputs as RTSP/HLS/UDP/RTP/RTMP Ethernet protocols. The Mini 150 supports one channel HD/SD live encoding and one IP stream out.

1.2 Architecture

Front Panel



- Power status indicator: This LED light is turned on when the encoder is powered on.
 Signal Lock status indicator: This LED light turns to green when a channel is locked.
 Otherwise the light turns to red.
- 2. Display screen: This LCD screen can show the management IP address, work mode, Input stream standard, output protocol, running status and etc.



Rear Panel

- 1. HDMI /AV /YPbPr/SDI IN port
- 2. RJ45-- management connection port
- 3. Power DC—DC Power connection
- 4. WiFi Antenna connectors

2 INSTALLATION

2.1 Installation Procedure



2.2 Preparation before Installation

Before installation, you should read through and confirm the following:

- Go through this user manual.
- Have knowledge of digital television system.
- Defined the sources, racks allocation, and set-up plan system wiring.
- Knows how to configure and operate this encoder.
- Go through related engineering design documents about the system.

2.3 Check Package and Contents

The MINI 150 package includes the following:

- Base Unit x1
- Power Supply x1
- HDMI cable x1
- WiFi Antenna x2
- RCA AV cable x1
- Flash Drive with User Guide x1

2.4 Equipment Wiring and Connection

To avoid electric shock and damage to the equipment, before setting up the wiring connection, please power off the equipment and all other connected external devices. Powering on the equipment only after all the wiring connection is completed.

2.4.1 Power Connection

Use the proper power connections is vital to the safe operation of the portable encoder. Only use the supplied 3-prong power connector or one with equal specifications. **Never** tamper or remove the 3rd-Prong grounding pin. This could cause damage to the Portable Encoder.

2.4.2 DC Power Connection

The MINI 150 encoder is intended to be use on either 120V or 240V systems. The power supply will automatically detect the system which is connected to. To hook up the power use the following steps:

1. Locate the DC power cord which is included with the MINI 150.

2. Plug the female end of the power cord (end with no prongs) into the back of the unit.

3. Locate a protected outlet (usually inside of the rack) to plug the male end of the power cable into.

2.4. 3 Connection Setup for Web Management

Connect the MINI 150 Management port with a network cable and set up a management network with the management PC. The default IP address is 192.168.1.106

2.4.4 Connection Setup for HDMI/CVBS/SDI signal input

Connect HDMI/CVBS/SDI signal to MINI 150 "HDMI IN"/"AV IN"/ "YPbPr IN"/"SDI IN" port with a HDMI /AV/YPbPr/SDI cable.

3 OPERATION GUIDE

3.1 Operating the Front Panel Interface

3.1.1 Powering Up and Initialization

Before powering-up the device, make sure that all cabling is correctly connected (refer to chapter 2.4 of this manual) and the device is correctly connected to the power supply.

Connect the Power port and the unit is powered up and starts the initialization.

The LCD screen lights up and displays the following:



The initialization takes about 20 seconds to complete, and then the LCD screen display as following:

192. 168. 1. 106 Mode. LIVE	
AV RTSP	
success	

Note: If the unit fails to initialize and hangs at the "booting" stage, switching off the device and then powering up again may help. If the device still fails to initialize, please contact your service representative for help.

3.1.2Front Panel Menu Structure

1 st Layer	2 nd Layer	3 rd Layer	4 th Layer			
	live	Playing Paused				
	Playback	Playing Paused				
	Record	Playing Paused				
		Work Mode Setting		Input	Auto HDMI/YPbPr SDI/AV	
				Output	UDP/RTP/RTSP/ HLS Live/RTMP	
			live	IP	x.x.x.x OK	
				Port	1234 ОК	
				Back		
	Setting		Playback	Mode	Sequence Play Single List Bandom	
Status				IP	x.x.x.x OK	
				Port	1234 OK	
				Back		
				Recorded	Recording Input	Auto HDMI/YPbPc SDI/AV
			Back			
					DHCP Enable/Disable	
				Mode	DNS Static/ Dynamic	
			Network		ОК	
		System			Back	
				Host IP/Gateway/ Mask/DNS	x.x.x.x	
					ОК	
					Back	
			AP	Wi-Fi ON/OFF Back		

		Version	SW/FW/HW version	
			Back	
		Pocovory	Yes/NO	
		Recovery	Back	
		Pohoot	Yes/NO	
		Rebool	Back	
		Back		
	Back			
Back				

Press "OK" to apply, press arrow up and down to move to other items.

3.2 Operating the WEB Interface

3.2.1 Access Interface

PC Web-GUI

The Mini 150 can be accessed and configured via web GUI. The accessing instruction is as the followings:

- Connect the "RJ45" port of the Mini 150 to a network switch and connect the management PC/server to the same network switch.
- 2. The **Mini 150 default IP address is 192.168.1.106**. Please modify the management server's IP address or Mini 150 IP address to be in the same IP section. To ensure that the equipment is smoothly connected to the network.
- 3. Open any web browser (e.g. Mozilla v30 or above, IE8.0 or above, safari, chrome v42 or above and etc.), input the equipment's IP address in format: <u>http://xxx.xxx.xxx.xxx.xxx</u> (xxx.xxx.xxx refers to Mini 150's IP address) and press ENTER button to confirm. The browser will attempt to connect to the device. If successful, a login page will appear. (see PIC-3.2.1)

User Name	
Password	
Sign in	



The default login info shows as below. Click "Sign in" button after input the correct user name and password.

User Name: admin

Password: admin.

Wireless connection to device:

Please refer to 3.3.6 System Wi-Fi Hotspot.

3.2.2 Main Interface

There are 3 working modes: Live, Playback and Recording. Click to enter desire working mode. (*PIC-3.2.2*)

Live Mode: to encode a live channel via HDMI/SDI/CVBS input and IP output.

Playback Mode: to play the recorded TS from the external USB disk.

Recording Mode: to record the encoded TS and store it to the external USB disk





3.2.3 Live Mode

To set the parameters for HD/SD channels encoding, as well as the broadcasting mode and parameters.



Basic Setting



This interface provides the main parameters of encoding and broadcasting. Please check and set
Page 15
NIAGARA VIDEO
CORPORATION

the parameter according to the following items:

- Input: Auto/HDMI/SDI/ YPbPr /AV source can be selected
- Output: support UDP/RTSP/HLS/RTP/RTMP/QAM protocol
- Mode: Ethernet / Ethernet or Wi-Fi can be selected
- Network Card: support Ethernet
- **IP/Port:** you can configure the IP streaming output address

live	A	dvanced S
input	HDMI	
Output	UDP	•
Mode	Ethernet Or Will Supports DVB only	•
Network Card	Wiff Hotspot	•
IP	227 • - 20 • - 30 • - 40	lø:
Port	1234	.igi

UDP Settings

Pic-3.2.2.1-1



RTSP Settings



HLS Settings





RTP Settings







RTMP Settings



Advanced Setting

To configure the advanced setting for encoding and streaming, please click the "Advanced" link in blue. It will take you to a new page to set the detailed parameters for **Live Mode**. It contains three parts of configuration: **Stream info, Video info** and **Audio info (Dolby D St Creator)**

Page 17 CORPORATION NIAGARA VIDEO

Advanced Settings		Back
Stream	Info	
Output Standard	DVB •	
Program Number	1	
Stream ID	0	
PMT PID	65	
PCR PID	68	
Total Bitrate	4692 🗄 Kbps	
Empty BitRate	100 😂 Kbps	
Program Name	HD_Program	
Provider Name	HD_Provider	

Pic-3.2.2.2

Stream info: In this page, you can configure the Output Standard, Program Number, Stream ID, PMT PID, PCR PID and etc.(Pic-3.2.2.2)

Video Info				
Video Source	+DMI -			
Video PID	66			
Video Encoding Mode	H264 -			
Video Resolution	• otus			
Aspect Ratio	• ctuA			
Video Bitrate Mode	CBR			
Video Bitrate	4000 😤 Khps			
IDR Interval	1			
Vic Mode	CABAC •			
Video Profile	High			
Video Level	H264 3 2			
GOP Structure	E6P .			
GOP Size	60 (2)			
GOP Close	Disable			

Note: For Empty BitRate, there may be a PCR error if set to 0!

Pic-3.2.2.3

- ♦ Video Info (refer to Pic-3.2.2.3)
 - Video Source: base on the source you selected in basic setting page

- Video PID: ranging from 32-8190
- Video Encoding Mode: DVB/MPEG
- Video Resolution: Auto/User can choose certain output resolution Resolutions Supported: HD: 1920 x 1080@24p/25p/30p/50i/60i,1280 x720@50p/60p/25p/30p SD: 720 x 576@50i, 720 x 480@60i
- Aspect Ratio: Auto, 16x9_Letter Box, 16x9_Cutoff, 4x3_Pillar Box and 4x3_Cutoff
- Video Bitrate Mode: CBR /VBR
- Video Bitrate: ranging from 800 to 14000Kpbs(MPEG2/H.264)
- IDR Interval: the range is 0-20
- Vic Mode: CABAC/CAVLC
- Video Profile: High/Main
- Video Level: H.264 3.0/ H.264 3.1/ H.264 3.2/ H.264 4.0/ H.264 4.1/ H.264 4.2
- GOP Structure: IBBP, IPPP,IBP,IBBBP
- GOP Close: Enable/Disable

Note: When input signal is detected and the preset output signal is of the allowed ones (see mapping table below), the preset will be remained, otherwise the output resolution will changed to Auto automatically.

input signal	preset output signal
1920x1080_30p	1920x1080_30p
	1280x720_30p
	720x480_60i
1920x1080_60i	1920x1080_30p
	1920x1080_60i
	1280x720_30p
	720x480_60i

1920x1080_24p	1920x1080_24p
1920x1080_50i:/	1920x1080_25p
	1920x1080_50i
	1280x720_25p
	720x576_50i
1280x720_60p:	1280x720_60p
	1280x720_30p
	720x480_60i
1280x720_50p	1280x720_50p
	1280x720_25p
	720x576_50i
720x480_60i:	720x480_60i
720x576_50i	720x576_50i

♦ Audio Info(Dolby D St Creator)

Audio Info (Dolty	D St Creator)	
Audet PID	516	10
Audio Encoding Mode	ACD	•
Auto Bitrite	1926	
AC3 AC Mode	2/0(L.R)	
Audio Volume	0	(4) dB
Audio Sampling Rate	48K	-



- Audio Source: HDMI Audio source could be selected
- Audio PID: ranging from 32-8190

- Audio Encoding Mode: AC3/MPEG1 Layer2/MPEG2 AAC-LC/MPEG4 AAC-LC
- Audio Bitrate: 128K/192K/256K/384K
- AC3 AC mode: 1+1(L,R), 1/0(C), 2/0(L,R)
- Audio Volume: -12 12
- Audio Sampling Rate: 48K is fixed output audio sampling rate

Click Apply button to make the new configuration into effect when finishing the setting.

Click Start button to make the encoding into effect;

Live Status

Live Video Status	
Statue	Free
Input Video Resolution	Ne Video
Output Bitrate	46DEKbps
Output Effective Bitrate	OKbps

Click the Status icon on the right-bottom to get reflect to the live status page. The page displays and updates the real-time status of encoding and streaming.

3.2.4 Playback mode

Basic Setting

- 1. Plug one USB disk to USB port on the front panel of the MINI 150 to play the TS from the disk.
- 2. Click the **PLAYBACK** icon to get the playback page, which will list all the available TS from the USB disk.
- 3. Click the required TS to play the TS.

File Name	
G G means-30170913174918-6 ht	
O O record 1-20170927153228-0 ts	
□ ◎ ● record_1.20170927152947-0.18	

Note: The Playback interface will save and display the TS list from memory of the last USB disk if there is no disk connected.



: to add new TS to the play list.

Live Settings

Live			Advanced Se	tings
Input	SDI			1
Output	UDP			
IP	225 🗘 + 1	t -1	\$ -16	\$
Port	2018			+

IP: The destination IP address for IP streaming.

Page 22 CORPORATION Port: The destination IP port for IP streaming.

Mode: Ethernet/Wi-Fi could be selected.

Network Card: Ethernet.

Daily play plan: To set the play plan.

Playback Status

This page displays the status of Playback.

Playing-back Status		
Status	Ready	

3.3.5 Recording Mode

Basic Setting

- 1. Connect the USB disk to the Mini 150.
- 2. Set the encoding parameter, and click the start icon to start the recording or pause to stop the recording.
- 3. Click the status icon to reflect to the Status page.

Input Auto Record Name record	Recording			Advanced Settings
Record Name. Pecord		Input	Auto	•
		Record Name	record	
Recording Loop		Recording	Loop	

Note: If the USB disk is not connected or there is not enough space on the disk, it is not able to start the recording. The minimum available free space is 10MB. The Mini 150 will overwrite the first file it created when the free space is not enough, all those files which are not created by Mini 150 will not be affected.

Recording Status

This page offers the status of the recording and the storage of the connected USB disk.

Recording Status	
Statue	17100
Input Video Resolution	No.video
Output Bitrate	4600Hbpy
Output Effective Bitrate	0x0pp
Record Name	record
USB Statue	USB does not easil
Recorded Time	00.00.00
Record Size	044

3.3.6 System

The System page provides the Network parameters, Language setup, time setup, upgrade, log and system info. (Pic-3.3.6.1)





♦ Network Status: This page shows status of network related info:

۲.	Network Status	
E filternet inte	oler	
	Statue	Approach feat
	MAC	40-09-06-06-00-00-0
	ie.	190,106.1.106
	Netmask	210.250.250.0
	Oxteway	102,100,3.1
	DNS	0800



✤ Ethernet: to set up equipment management access IP address, Subnet Mask, Gateway and

etc.(see Pic-3.3.3.3) The MINI 150 can be configured to use DHCP to obtain an IP address/Subnet Mask/Gateway. To obtain an IP address may require up to one minute.

					DHCP	on
	102	-160	10-1	<u> 0</u>]-106	-	105.5
Submet Mask	258	(a) (255	(R) - 255	s]-b	限	
Gataway	192	0 -100	(0) 1	(d)-1	10	
	er Eutoret Mask Gateway	III 102 Eutonet Mask 255 Gataway 162	#* 102 102 -160 Batterier Mareit 205 30 -255 Gateway 102 102 102 -108	# 102	# 102 38 -168 36 1 36 -106 Batternet Manes 255 36 -255 36 -9 Gateway 162 161 161 161 -1	DHCP 102 (B)-160 (B)-1 (B)-706 (B) Submer Marek 255 (B)-255 (B)-255 (B)-0 (B) Gateway 162 (B)-108 (B)-1 (B)-1 (B)

Pic-3.3.6.3

♦ Wi-Fi Hotspot:

This page shows how to set up a Wi-Fi Hotspot which enables a PC, phone or Tablet to log in via wireless connection to the device.

 Control (1998) 	Wifi Hotspot		ON
	SSID	NB100-0c-42-fb	
	Mode	Auto	·
	Channel	Auto	•
	Encrypt	ON	
	Password	12345678	

♦ Wi-Fi

The Mini 150 can connect to a WiFi Network.

<	Wifi		ion i
Witi Name		Status	
Katy periy			1
velar_test			
AVIF-61502091158	r -		6
MY WHI			
velay-office3			
testa for jo			
mgaE2x80x994			
LeBatWiFi151			

Note: Wi-Fi hotspot and Wi-Fi reception have the same range. When it is used as a hotspot, Wi-Fi reception is disabled automatically, vice versa.

♦ Time: to configure the system time with Manual or Internet time.

Sync Mode	Auto
System Time	Auto Manual Infernet

Pic-3.3.6.5

Upgrade: to upgrade new version software by selecting a file and clicking the Arrow button.
 It will take several minutes to finish the upgrading and after that, it will need to be rebooted.(Refer to Pic-3.3.3.6)

<	Upgrade			
Select a file				1
		Start-up Mode	Normal Start	•

Pic-3.3.6.6

Development: to export and clear the logs, check the debug info, export configuration, export& upgrade license and view system information.

<	Development	
Logs		•
Debug		•
Configuration		•
License		>
System Information		•



Logs: User can export and clear the logs in this interface.

	🗢 🌡			1.	f
<	ι ι	Logs			
	Export logs Cit	ear logs			



Debug: User can check the debug info which is usually used for R-D.

< Debug	
2 DEBUG	
ALARM	
EMERGENCY	
D LOG	
₽ SYS	
UDP	

Pic-3.3.6.7-2

Configuration: User can export configuration (including system and service configuration) in this tab.

NI AGATA	œ 🗢 🛔	1	o A
<	Configuration		
E	port configuration		

Pic-3.3.6.7-3

License: User can export and upgrade the license, a reboot is needed to active the license.

La cata	♥ 1	10 1
٠	License	
Select	afie	Import
Ret	eat	Export

System information: User can check the system info in this tab.

NIAGARA 🗖 😤 🌡	L 🔯 1	h
< System Information		
Software Version	1.7.8	
Firmware Version	1.0.0	
Hardware Version	0.0.99	
Driver	Getting	
Encode Firmware	3c-1-6	
SPI ROM	Getting	

Pic-3.3.6.7-5