

Niagara® 9300L Digital Input Models

Linux based Encoding and Transcoding Systems – HEVC, H.264 and MPEG-2



Different models to fit a variety of needs.

The Niagara 9300L series is a Linux based high-density/high-performing multi-channel encoder/transcoder for service providers, broadcasters, and enterprises. The Niagara 9300L SDI input models support HD and/or SD SDI inputs with up to 8 stereo pairs (16 channels) of embedded audio.

High Density

Configure the Niagara 9300L with two, four or eight independent channels in this 1RU system for applications that require high density.

Enhance Efficiencies

Optimize your workflow by easily developing customized solutions with the powerful and accessible web SDK or via SNMP.

Exceptional Performance

With the latest high-performance multi-core and Intel XEON processing technology, deliver multiple simultaneous streams in a variety of formats to extend existing audiences and reach new ones, such as mobile, web, and IPTV users.

Comprehensive and Adaptable

All industry encoding formats are included on one system as standard.

Ideal Solutions

- > Content delivery networks
- > Corporate Video Delivery

Applications

- > Live streaming / simulcasting
- > Webcasting
- > Mobile TV
- > IPTV

Key Attributes

- > Live capture, encoding and streaming for professional-grade digital video and audio delivery
- > Configurable video/audio inputs
- > Individually brand streams with bitmap overlays (e.g., logos and graphics)
- > Web interface and SNMP provide remote setup, control and monitoring
- > High-efficiency power supply



Delivering Video Whenever, Wherever

Niagara® 9300L Digital Models

Encoder/Transcoder

Niagara 9300L-TR

Transcode only – MPEG-TS Inputs



Back View

Niagara 9300L-2D

Video: - 2 HD or SD SDI (2 x DIN)

Audio: - Embedded SDI

(8 stereo pair per SDI input)



Back View

Niagara 9300L-4D

Video: - 4 HD or SD SDI (4 x DIN)

Audio: - Embedded SDI

(8 stereo pair per SDI input)



Back View

Niagara 9300L-8D

Video: - 8 HD or SD SDI (8 x DIN)

Audio: - Embedded SDI

(8 stereo pair per SDI input)



Back View

SDI Inputs comply with SMPTE 259M, 292M and 424M

Specifications

Encoding Formats:

- Adobe® Flash® H.264* (RTMP and RTMPS)
- NDI
- SRT
- Apple® HTTP Live Streaming (HLS)
- Dynamic Adaptive Streaming over HTTP (MPEG-DASH)
- Microsoft® Live IIS Smooth Streaming
- MPEG 2 Transport Stream (UDP or RTP)
- H.264 and HEVC codecs

Transcoding:

- Video Codec Inputs: MPEG-2, H.264 and HEVC
- Audio Codec Inputs: MPEG-1 Layer II, AAC-LC, HE-AAC v1/v2, Dolby Digital (AC-3), Dolby Digital Plus (E-AC-3)
- Transcoding Inputs: MPEG-TS, RTMP, RTSP, HLS

Pre-Processing:

- Adaptive de-interlacing
- Video cropping and rescaling
- Aspect-ratio conversion or pass-through

- Frame rate down and up-conversion
- Video preview
- Logo & Slate insertion
- Time code/Date&Time insertion
- Closed-caption support

Software:

- SCX-L (SCX Linux version)
- SNMP
- Web SDK (REST API)

Connectivity:

- 4x1GB Ethernet

Dimensions:

1U rack mount appliance (1RU x 17" W x 27.8" D)

Weight:

- 41 lbs. (18.6 Kgs)

Power:

- 750 W redundant power supplies
- NEMA 5-15 type connector

Delivering Video Whenever, Wherever

© 2020 Niagara Video Corporation Niagara®, GoStream® and Niagara SCX® (and design)™ are registered trademarks of Niagara Video. Flash is a trademark of Adobe Systems Inc. iPad, iPod and iPhone are registered trademarks of Apple Inc. All other trademarks are the property of their respective owners. Product specifications and availability may change without notice.